

HP.
mosaics





**Amalfi
HP12BA
(Glossy)**



**Bari
HP12BB
(Glossy)**




**Cayo CoCo
HP12BCC
(Glossy)**



**Denim Copper
HP12BDC
(Shiny)**



**Forrest Blue
HP12BFB
(Glossy)**



**Iria
HP12BI
(Glossy)**



**Kara Beige
HP12BKBG
(Glossy)**



**Kara Blue
HP12BKB
(Glossy)**



**Lungomare
HP12BL
(Glossy)**



**Matte
Abuhna
HP12BMA
(Matte/Shiny)**



**Matte
Arabescato Gold
HP12BMAG
(Matte/Shiny)**



**Matte
Beray
HP12BMB
(Matte/Shiny)**



**Matte
Black Rock
HP12BMBR
(Matte)**



**Matte
Brescia
HP12BMBRE
(Matte)**




**Matte
Ivet
HP12bmiv
(Matte)**



**Matte
Shabby Terra
HP12BMST
(Matte)**




**Matte
Yada
HP12BMY
(Matte)**



**Print
HP12BP
(Glossy)**




**Saona
HP12BS
(Glossy)**



**Tanzanite
HP12BTAN
(Glossy)**



**Tozen
HP12BTOZ
(Glossy)**



**Umbria
HP12BUMB
(Glossy)**











**Verona
HP12BV
(Glossy)**



Connect with Us!
98% RECYCLED GLASS
Made in Spain

BRICK - 1"x2" GLOSSY

| QUALITY CHARACTERISTICS | NORM | STANDARDS | RESULT |
|---|--------------|---|----------------------------|
|  Water absorption of the body | ISO 10545-3 | ISO 10545-3 | None |
|  Breaking strength | ISO 10545-4 | | |
|  Abrasion resistance | ISO 10545-7 | MOHS | 4 |
|  Frost resistance | ISO 10545-12 | ISO 10545-12 | Resistant |
|  Chemical resistance | ISO 10545-13 | Domestic Products Pool Water Additives Low Acid + Alkalins High Acid + Alkalins | GA GA GLA GH A |
|  Thermal shock resistance | ISO 10545-9 | ISO 10545-9 | Resistant |
|  Dynamic coefficient of friction | BOT 3000E | ANSI A 137.1 | N/A |
|  Shade Variation | See Below | Substantial Variation | V4 |

Colors Featured in HP Brick 1"x2" Glossy Finish:

Amalfi, Bari, Cayo Coco, Forest Blue, Iria, Kara Beige, Kara Blue, Lungomare, Print, Saona, Tanzanite, Tozen, Umbria, Verona



Uniform appearance

V1



Slight Variation

V2



Moderate Variation

V3











Substantial Variation

V4

For the best product laying results, material from at least three boxes should be mixed.



BRICK - 1"x2" MATTE

| QUALITY CHARACTERISTICS | NORM | STANDARDS | RESULT |
|---|--------------|--|----------------------------|
|  Water absorption of the body | ISO 10545-3 | ISO 10545-3 | None |
|  Breaking strength | ISO 10545-4 | | |
|  Abrasion resistance | ISO 10545-7 | MOHS | 5 |
|  Frost resistance | ISO 10545-12 | ISO 10545-12 | Resistant |
|  Chemical resistance | ISO 10545-13 | Domestic Products Pool Water Additives Low Acid + Alkalins High Acid + Alkalins | GA GA GLA GH A |
|  Thermal shock resistance | ISO 10545-9 | ISO 10545-9 | Resistant |
|  Dynamic coefficient of friction | BOT 3000E | ANSI A 137.1 | See Below |
|  Shade Variation | See Below | Slight Variation | V2 |

Colors Featured in HP Brick 1"x2" Matte Finish:

Abuhna Matte, Arabescato Gold Matte, Beray Matte, Brescia Matte, Matte Black Rock, Matte Ivet, Shabby Terra Matte, Yada Matte

Dynamic Coefficient of Friction:

0.42: Abuhna Matte, Shabby Terra Matte, Yada Matte

0.60: Arabescato Gold Matte, Beray Matte, Brescia Matte, Matte Black Rock, Matte Ivet



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation











V4

Substantial Variation

For the best product laying results, material from at least three boxes should be mixed.



BRICK - 1"x2" MATTE & SHINY

| QUALITY CHARACTERISTICS | NORM | STANDARDS | RESULT |
|---|--------------|--|----------------------------|
|  Water absorption of the body | ISO 10545-3 | ISO 10545-3 | No |
|  Breaking strength | ISO 10545-4 | | |
|  Abrasion resistance | ISO 10545-7 | MOHS | 4 |
|  Frost resistance | ISO 10545-12 | ISO 10545-12 | Yes |
|  Chemical resistance | ISO 10545-13 | Domestic Products Pool Water Additives Low Acid + Alkalins High Acid + Alkalins | GA GA GLA GH A |
|  Thermal shock resistance | ISO 10545-9 | ISO 10545-9 | Yes |
|  Dynamic coefficient of friction | BOT 3000E | Not Applicable; Wall Tile Only | |
|  Shade Variation | See Below | Moderate Variation | V3 |

Colors Featured in HP Brick 1"x2" Matte Finish:

Denim Copper



V1

Uniform appearance



V2

Slight Variation



V3

Moderate Variation



V4

Substantial Variation

For the best product laying results, material from at least three boxes should be mixed.

